



## D358

### Key Features

Day/night functionality, Smart IR, up to 30m (98 ft) IR distance, Up to 120 dB Optical WDR(Wide Dynamic Range), 2D/3D DNR (Digital Noise Reduction), Ultra 265, H.265, H.264, MJPEG, Embedded smart algorithm, Triple streams, ROI (Region of Interest), 9:16 corridor mode, ONVIF Conformance, Support PoE power supply, Built-in PoE splitter that outputs DC 12V, Wide temperature range: -40°C to 60°C (-40°F to 140°F), Wide voltage range of  $\pm 25\%$ , IK10 vandal resistant, IP67

Exsom EIPC-D358 ( F2.8~12)	
Resolution	8MP (3840×2160)
Sensor	1/2", 8.0 megapixel, progressive scan, CMOS
Lens	2.8~12mm@F1.5
Angel of View	114.8°~47.3°
Defog	Digital Defog
Minimum illumination	Colour: 0.003 Lux (F1.6, AGC ON)0 Lux with IR on
IR Range	30m
WDR	120 dB
Video Compression	Ultra 265, H.265, H.264,MJPEG
Frame Rate	8MP (3840×2160): Max. 15 fps
Working Environment	-40°C ~ +60°C
hardware facilities	IP67 – IK10- Micro SD up to 128GB-Alarm I/O
Intelligent Identification	Intrusion, cross line, motion detection, Face detection, Audio detection, People counting, Defocus, Scene Change